



ART. 44084

Waste oil gravity and suction drainers

Combination air operated oil suction drainer 80 litre without transparent chamber



FLUIDS

WASTE OIL

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION

CERTIFICATIONS

PRESSURE EQUIPMENT DIRECTIVE

| Features | UM | Value |
|-----------------------------------|---------------------|---------------|
| Tank capacity | litres | 80 |
| Max draining capacity | litres | 62 |
| Prechamber capacity | litres | - |
| Bowl capacity | litres | - |
| Air pressure for depressurisation | bar | 6,5 ÷ 7 |
| Depressurisation time | min | 2,5 - 3 |
| Noise level | dB | 75 |
| Suction speed | l/min | 1,5 ÷ 2 |
| Total suction capacity | litres | 60 ÷ 65 |
| Discharging/Suction hose | m | 2/2 |
| Max pressure for discharging | bar | 0,5 |
| Set of probes | P/N | 45560 |
| Packing | N° - m ³ | 2 - 0,189 |
| Weight | kg | 34 |
| Dimensions (A-B-C) | cm | 62 - 42 - 136 |
| Dimensions (D) | cm | 166 |

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.