

21A N.C./N.O.



FEATURES

- Wide range of application valves for liquids and gas
- Reliable proven design with high flow
- Small poppet valve for tight shutoff
- Wide range of elastomers
- Mountable in any position

TECHNICAL SPECIFICATION

- Body material:** Brass UNI EN 12165 CW617N
- Armature tube:** Stainless Steel AISI 300 series
- Plungers:** Stainless Steel AISI 400 series
- Spring:** Stainless Steel AISI 300 series
- Media:** mineral oils, gasoline, diesel, fuel oils water, air, inert fluids, inert gases, steam
- Ambient temperature:** See coils catalogue page for its compatibility
- Fluid temperature:** -10°C +140°C with FKM and EPDM seals
-10°C +90°C with NBR seals
-40°C +180°C with PTFE and RUBY seals
- Max allowable pressure (PS):** 40 bar
- Protection class:** IP65 (complete with electric plug)
IP67 (with antiumidity kit can be rated to IP67)
- Electrical conformity:** IEC 335
- Switching time:** 20 - 40 msec (depending on pressure conditions)

AVAILABLE ON REQUEST

- Low lead brass for food grade
- Nickel plated version
- NSF approved version
- Double spring for higher operative pressure
- High pressure up to 100bar (see High Pressure section)
- Compressor flange interface (i.e. 4690KV20 see Drawing reference 1a)
- Manual override (i.e. 21A3KV15-M)
- Explosion proof coil Ex m (see Atex section)
- Explosion proof coil Ex d (see Atex section)
- Explosion proof coil Ex nA (see Atex section)
- Latching coil (See coil section)



21A	1	K	V	15	21A	**	B	D	A	08	024	A	S
Model valve	B= Flange	K= N.C.	V= FKM	10	Orefice 10*mm	D= for 8W coil G= for 12W-14W coil	B= 30mm Ø 13	D EN 175301-803	B= Class F	08= 8W	024= 24V	C= DC	S= Without Approval
	1= G 1/8	Z= N.O.	B= NBR	20			U= 36mm Ø 13		V= Class H	12= 12W	112= 110V-120V	A= AC	Y= UL, CSA, VDE
	2= G 1/4	E= EPDM	T= PTFE	25			G= 52mm Ø 13		14= 14W	223= 220V-230V	D= AC		
	3= G 3/8	R= RUBY	45										
4= G 1/2		55											

(**) Only for N.O. version

PIPE	Ø (mm)	Kv (l/min)	MAX VISCOSITY cSt (°E)	PRESSURE min	PRESSURE MAX MOPD (bar)						GAS CODE	NPT CODE	DRAWING REFERENCE
					COIL TYPE								
					AC			DC					
					B	U	G	B	U	G			

Normally Closed

Flange	1,5	1,4	12(2)	0	30	-	-	18	-	-	21A1KV15	1
	2	2	37(5)		22	35	35	16	30	30	21A1KV20	1
	2,5	3,2	53(7)		14	30	30	9	25	25	21A1KV25	1
G 1/8	1,5	1,4	12(2)	0	10	25	25	6	18	20	21A1KV30	1
	2	2	37(5)		30	-	-	18	-	-	21A3KV15	2
	2,5	3,2	53(7)		22	35	35	16	30	30	21A3KV20	2
	3	4	53(7)		14	30	30	9	25	25	21A3KV25	2
	4,5	6,5	53(7)		10	25	25	6	18	20	21A3KV30	2
G 1/4	1,5	1,4	12(2)	0	5	12	12	2	7	8	21A3KV45	2
	2	2	37(5)		30	-	-	18	-	-	21A2KV15	2
	2,5	3,2	53(7)		22	35	35	16	30	30	21A2KV20	3
	3	4	53(7)		14	30	30	9	25	25	21A2KV25	3
	4,5	6,5	53(7)		10	25	25	6	18	20	21A2KV30	3
G 3/8	5,5	9	53(7)	0	3	7	10	1	2,5	5	21A2KV55	3
	4,5	6,5	53(7)		5	12	12	2	7	8	21A5KV45	4
	5,5	9	53(7)		3	7	10	1	2,5	5	21A5KV55	4
G 1/2	4,5	6,5	53(7)	0	5	12	12	2	7	8	21A8KV45	5
	5,5	9	53(7)		3	7	10	1	2,5	5	21A8KV55	5


(Part numbering example add "N" at the 4th digit 21AN2KV20)

Normally Open


Flange	1,5	1,4	12(2)	0	25	-	-	25	-	-	21A12V15D	1
	2	2	37(5)		20	-	-	20	-	-	21A12V20D	1
	2,5	3,2	53(7)		14	-	-	14	-	-	21A12V25D	1
G 1/8	1,5	1,4	12(2)	0	10	-	-	10	-	-	21A12V30D	1
	2	2	37(5)		25	-	-	25	-	-	21A32V15(*)	2
	2,5	3,2	53(7)		20	30	30	20	30	30	21A32V20(*)	2
	3	4	53(7)		14	17	17	14	17	17	21A32V25(*)	2
	4,5	6,5	53(7)		10	15	15	10	15	15	21A32V30(*)	2
G 1/4	1,5	1,4	12(2)	0	5	6	6	4	-	6	21A32V45(*)	2
	2	2	37(5)		25	-	-	25	-	-	21A22V15(*)	2
	2,5	3,2	53(7)		20	30	30	20	30	30	21A22V20(*)	3
	3	4	53(7)		14	17	17	14	17	17	21A22V25(*)	3
	4,5	6,5	53(7)		10	15	15	10	15	15	21A22V30(*)	3
G 3/8	5,5	9	53(7)	0	4	6	6	4	-	6	21A22V45(*)	3
	4,5	6,5	53(7)		2,5	3,5	3,5	2,5	-	3,5	21A22V55(*)	3
	5,5	9	53(7)		4	6	6	4	-	6	21A52V45(*)	4
G 1/2	4,5	6,5	53(7)	0	2,5	3,5	3,5	2,5	-	3,5	21A52V55(*)	4
	5,5	9	53(7)		4	6	6	4	-	6	21A82V45(*)	5
					2,5	3,5	3,5	2,5	-	3,5	21A82V55(*)	5

(Part numbering example add "N" at the 4th digit 21AN2KV20)

(*) D for B Coil; G for U/G coil



REPAIR KIT
Normally Closed
Orifice <=3mm: KT130KV30-A
Orifice >=3mm: KT130KV55-A




REPAIR KIT
Normally Open
Coil B type (8W)
Orifice <=3mm: KT130ZV30-G
Orifice >=3mm: KT130ZV55-F
KT130KV55-A
Coil U type (12W)
Coil G type (14W)
Orifice <=3mm: KT130ZV30-G
Orifice >=3mm: KT130ZV55-G

RELATED ITEMS


- P990305: Electrical plug EN 175301-803 Pg9
- P990306: Electrical plug EN 175301-803 Pg11
- P992126: Electrical plug EN 175301-803 Pg9 (with OR screw)
- P992127: Electrical plug EN 175301-803 Pg11 (with OR screw)
- P992128: Electrical plug EN 175301-803 cable 2 wires, 53cm
- R452714: Antiumidity kit (up to IP67 protection together with plugs P992126, P992127; P992128 & H coil class)
- P992087: Timer for automatic switch

Drawing Reference



INSTALLATION

- The solenoid valves can be mounted in any position
- Other port connections available on request
- Maintenance and instruction sheet available in each solenoid valve box
- Availability of repair kit and coils as spares



Dimensionale Table

Figure	Coil Type	D mm	E mm	F mm
1-1a-2-3-4-5	B	30	42	56
	U	36	48	60
	G	52	55	67

