

Oil-Rite Corporation

4325 Clipper Drive, P.O. Box 1207

Manitowoc, WI. 54221-1207

Phone: (920) 682-6173 • **Fax:** (920) 682-7699**Email:** sales@oilrite.com • **Web Address:** www.oilrite.com**Item # B4767-3B, 303 Stainless Steel Window Flow Sight with Ball Indicator, 3/8" Female NPT Inlet, 3/8" Female NPT Outlet**

Window Flow Sights with Ball Indicator have an air-tight glass sight that allows visual observation of liquid flow, clarity, and condition. A nylon ball indicator shows the direction of fluid movement.

The body is 303 stainless steel. The glass sight has a pressure tight, solid gasket design with Buna-N seals. This flow sight features a 7/16" diameter off-white nylon ball to visually indicate fluid movement. The flow of fluid will position the ball toward the outlet.

The unit can be installed in any position (horizontally, vertically, or at an angle).

It tolerates temperatures up to 180° F. The maximum recommended pressure is 125 PSI. The total height is 4 5/64" and the hex size is 15/16". The visible area of the glass sight is 1 3/8" in length.

NOTE: This image is a general illustration of a window flow sight with ball indicator. It is not an exact representation of the part described on this page.

**Specifications**

Feature	Ball Indicator
Inlet	3/8" Female NPT
Outlet	3/8" Female NPT
Max Pressure	125 PSI
Sight Material	Glass
Body	303 Stainless Steel
Seals	Buna-N